

ONLY FROM

nemco[®] | FOOD
EQUIPMENT

Easy Onion Slicer 2™

Takes EASY to a whole new level . . .

Because a factory-pretensioned blade set never, ever, needs tightening!



ROBINEX
BEDRIJFSKEUKENS

H.L.Breenkade 1, 2465 AL Rijnsaterwoude
Tel: 0172-500280 e-mail: info@robinex.nl
www.robinex.nl

Buy once. Buy the original.
Always look for this mark of quality





Self-Taut

Equipped with a cartridge blade assembly that's pretensioned, the advanced 2 version of Nemco's famous Easy Onion Slicer takes labor savings and operator safety to a whole new level. Now slicing onions and other firm veggies and fruits is truly EASY!

Blades Are Pretensioned . . . And Stay Tensioned!

Designed as a single, modular cartridge, the blade set is properly aligned and tensioned at the factory. As a result, the blades require absolutely ZERO tightening—not out of the box, not after heavy use in the busy commercial kitchen. Instead, your employees:

- Save time by doing more slicing and less fiddling with the blades.
- Achieve and maintain better slicing consistency.
- Reduce blade exposure for optimum safety.

More Reliable Performance

Just like its predecessor, the Easy Onion Slicer 2 features stainless steel blades and commercial-grade aluminum construction for lasting durability. And yet, even better is the new cartridge blade set, which:

- Maintains proper blade tension for more precise, uniform slicing.
- Promotes longer blade life—the blades remain in correct alignment, thus avoiding contact with the pusher block that can dull or damage the sharp edge.
- Requires absolutely ZERO tightening, ever, for extremely simple blade removal, cleaning and replacement.

Safer and More Efficient

Built for versatility, the Easy Onion Slicer 2 cuts everything from the colossal onions to celery, potatoes, green peppers, firm tomatoes, cucumbers and citrus fruits, such as lemons, limes and oranges. And through it all, a number of special features optimize efficiency.

- The blade cartridge design promotes optimum safety, enabling even your most inexperienced employees to change out the blades in a snap.
- The slicer's vertical drive and ergonomic handle use the power of mechanical leverage to take all the effort out of cutting and minimize operator fatigue.
- The legs are built tough for maximum stability and are specially formed to accommodate placing a food pan right beneath the blades.

Top-down drive and ergonomic handle take the work out of slicing

With a simple pull of this pin, the pusher assembly comes off for cleaning or a quick change out when switching to a new blade set of a varying slice width

Blades are razor-sharp stainless steel

Sturdy legs stabilize unit for smooth slicing

Rubber feet prevent slipping



Suggested Uses

Ideal for onions, celery, potatoes, pickles, firm tomatoes, oranges, lemons and limes.

General Specifications

Model	Description	Slice Diameter
56750-1	3/16" Slice	Up to 4"
56750-2	1/4" Slice	Up to 4"
56750-3	3/8" Slice	Up to 4"
56750-4	1/2" Slice	Up to 4"

Optional Accessories

56539-1:	3/16" Cartridge Blade Assembly (17 blades)
56539-2:	1/4" Cartridge Blade Assembly (13 blades)
56539-3:	3/8" Cartridge Blade Assembly (9 blades)
56539-4:	1/2" Cartridge Blade Assembly (7 blades)

Dimensions

Equipment (w x d x h)	10" x 19" x 30"
Shipping Carton (l x d x h)	20 1/2" x 11" x 21"
Equipment Weight	17 lbs
Shipping Weight	22 lbs

Replacement parts are available through Nemco's 24-hour Zip Program.

Nemco reserves the right to make design, specification or model changes without notice.



Thanks to a pretensioned blade cartridge, even your most inexperienced employees can easily change the blades for optimum safety. Plus, they'll save time and slice with impeccable consistency.



nemco® | FOOD EQUIPMENT

Physical Address: Corporate HQ
301 Meuse Argonne | Hicksville, OH 43526
800.782.6761 • 419.542.7751 • f: 419.542.6690

Mailing Address:

PO Box 305 | Hicksville, OH 43526

Nemco West Distribution Center/Test Kitchen
4300 E Magnolia Street | Phoenix, AZ 85034

NemcoFoodEquip.com



Printed 4/19. Printed in the USA.